



Genexis FiberTwist

P3000B-Series Point-to Point (PtP)

Compact network demarcation with optional routing

The highly successful FiberTwist P2000 and P3000-Series have proven themselves as flexible, reliable and fully manageable Point-to-Point Network Terminators. To further meet future market demands, a new platform generation will provide even more possibilities, like upgrading the device to a router using the same hardware.

With the FiberTwist product range, Genexis introduces a unique broadband connectivity solution that redefines size, ease of installation and flexibility for the distribution of fiber bandwidth throughout the entire home.

Key features

- Compact, fully managed Point-to-Point network demarcation
- Patented FiberTwist twist-on interface that fits all FiberTwist FTUs and Bracket; enabling a trouble-free, real DIY end-user installation
- Up to 4 Gigabit LAN ports to connect external devices, such as a Residential Gateway and various Layer 2 services
- Optional integrated CATV receiver or FXS port
- Flexible management via i.a. TR-069 and CloudSight
- ITU-T K.21 Basic level (Surge Protection)
- Halogen-free PCB
- Dying gasp support
- Enhanced LED dimming
- Upgradable to L3/routing via license fee

A perfect Match for every deployment scenario

The Genexis FiberTwist product family has been developed in such a way that it can be integrated into various deployment models, including single-dwelling and multi-dwelling scenarios. Using products from the FiberTwist FTU family, the demarcation point can be extended to any desired location in the home, enabling easy access and installation of services.

Its small size (110 x 110 x 46 mm) makes the FiberTwist a perfect fit in any environment, be it a living room, metering cabinet or basement.

The FiberTwist P3000B-Series is using the open and flexible GenXOS operating system, based on ioWrt. This offers operators maximum software flexibility in every deployment scenario.



Product features and specifications

Genexis FiberTwist P3000B-Series Point-to Point (PtP)

General specifications		User interfaces		Quality of Service (QoS)	
Dimensions (H x W x D)	110x110x46 mm	1 x Unlock button		4 QoS traffic classes	
Operating temperature	0 - 45 °C	1 x LED dimming button		Port based QoS	
Storage temperature	-20 - 75 °C	4x LAN interface		IEEE 802.1p tagged frames	
Operating humidity (non-condensing)	5% -95%	1 x Power connector		IPv4 QoS Type of Service (ToS)	
Storage humidity (non-condensing)	5% -95%	1 x Reset button		IPv4 QoS Differentiated Services (DS)	
Flame retardants	Halogen free	1 x CATV output coaxial F-female*		IPv6 QoS Traffic Class	
Power supply voltage	12 Vdc ± 5%			Strict, weighted, or mixed mode per port	
Power consumption (EU-CoC-BBE)		CATV*		Management	
P3410B & P3411B	2.8 W Idle Mode	Wavelength (typical)	1550 nm	DHCP/TFTP, HTTP	
	4.4 W On Mode	Optical return loss	min 45 dB	TR-069, TR-181	
P3414B	3.2 W Idle Mode	RF passband	45-900 MHz	CLI	
	5.3 W On Mode	RF output impedance	75 Ω	CloudSight	
P3420B	5.5 W Idle Mode	F-Connector length	11 mm	Ethernet OAM including dying gasp	
	6.9 W On Mode	AGC optical input power	-9 ... 0 dBm	GUI	
Fiber (WAN) interface		RF output level (AGC on) according to CENELEC-42	80 ± 2.5 dBμV 4% OMI / ch	Emissions and safety regulations	
Optics compliant with 1000BASE-BX20-U		RF flatness	max 2 dB	CE approved	
TX wavelength (typical)	1310 nm	Output return loss	max -10 dB	LVD safety standard:	
RX wavelength (typical)		Slope / tilt	1 ... 4 dB	· IEC EN 62368-1:2014	
· FiberTwist P3410B	1490 & 1550 nm	CNR min	47 dB@-8 dBm	· A11 2017 (Second Edition)	
· FiberTwist P3411B	1490 nm	CSO / CTB	max -57 dBc	Laser safety standard:	
· FiberTwist P3416B	1490 & 1550 nm	Spurious to carrier	max -57 dBc	· IEC EN 60825-1: Class 1 laser	
· FiberTwist P3420B	1490 nm (CATV 1550 nm)	MER QAM-64	> 34	Emissions & Immunity standards:	
Single mode fiber	ITU-T G.657.A2	MER QAM-256	> 36	· EN 55032/CISPR 32:2015 ED2.0, Class B	
Optical connector	SC/APC	Remote enabling of CATV		· EN 55035:2017	
Optical Range	Up to 20km	Layer 2 features		· EN 55024:2010 / A1:2015	
Digital Diagnostic Monitoring (DDM)		Jumbo up to 2K supported on WAN and LAN		· EN 50083-2	
Configurable optical blackout (for OTDR)		Non-blocking switching performance		RoHS/WEEE marking	
LAN interfaces		Up to 8K MAC addresses		Surge protection:	
4x 10/100/1000Base-T RJ45 ports		Automatic learning and aging		· Compliant with ITU-T K.21 basic level	
LED indicators for speed and activity		IEEE 802.1Q VLAN support for 4096 VLANs		Status LEDs	
IEEE802.3az Energy Efficient Ethernet (EEE)		VLAN classification and retagging (VLAN mapping)		System/Status	⏻
IGMP		Port-based VLANs		Fiber uplink	⏪ ⏩
IGMP/MLD (v2/v3) snooping and proxy		IEEE 802.1ad QinQ VLAN tagging		CATV status*	📺
Configurable parameters for e.g. robustness, fast leave and snooping behavior		Port Trunking and Monitoring/Mirroring			
		Layer 2 loop prevention			

* Applicable to selected models only

Genexis FiberTwist P3000B-Series product models

Model	Type	WAN (Mbps)	LAN interface	Wavelength			
				TX	RX	CATV	Voice (FXS)
FiberTwist P3410B	Network termination with router functionality	1000	4x	1310 nm	1490 nm & 1550 nm	-	-
FiberTwist P3411B	Network termination with router functionality	1000	4x	1310 nm	1490 nm	-	-
FiberTwist P3416B	Network termination with router functionality	1000	4x	1310 nm	1490 nm & 1550 nm	-	Yes
FiberTwist P3420B	Network termination with router functionality	1000	4x	1310 nm	1490 nm	1550	-

Note: More features are available and not listed in this document. Not every listed feature may be included in the shipping product.

We reserve the right to make changes of technical specifications, housing or design without prior notice..